

XGN-T系列轮胎式移动破碎站

XGN-T series tire type mobile crushing station



XGN-T系列轮胎式移动破碎站，是在传统移动破基础上通过技术改进而设计出的可以一次破碎成型的移动破碎站，其采用轮胎底盘，性价比高，油电两用，转场方便，与同等型号相比，具有一次破碎成型，可吃大料，产量更高，能耗更低的优点。

XGN-T series tire-type mobile crushing station is a mobile crushing station that can be crushed and formed at one time, which is designed on the basis of traditional mobile crushing through technical improvement. it adopts a tire chassis, which is cost-effective, dual-use for oil and electricity, and convenient for transition. Compared with the same model, it has the advantages of one-time crushing and molding, large-scale raw materials, higher output, and lower energy consumption.

突出优势

>> Highlight the Advantages

1、机动性强

轮胎式破碎站长度、轴距短，转弯半径小，可以在普通公路和作业区内灵活行驶；

2、一体化整套机组

消除了繁琐的安装作业，减少停机时间，且合理的空间布局提高了场地驻扎的灵活性；

3、一次破碎成型、按需定制

石灰石破碎，替代颚破+反击破，一次破碎成型；可根据不同破碎工艺要求，进行多元化设备配置；

4、单机产量高、运输成本低

最大进料粒度在75公分，时产量可达320吨；可以在现场直接加工物料，降低运输成本；

5、油电两用、出料可调

可油电两用，停电不停工；无篦条+自流槽设计，出料可调节，避免过粉碎现象，粒型更圆润，符合高标准用料要求。

1. Strong mobility

The tire-type crushing station has a short length, a short wheelbase, and a small turning radius, allowing it to drive flexibly on ordinary roads and work areas;

2. Integrated whole unit

Eliminate tedious installation work, reduce downtime, and reasonable space layout improves the flexibility of the site;

3. One-time crushing and forming, customized on demand

Limestone crushing, instead of jaw crushing + impact crushing, one-time crushing and forming; according to different crushing process requirements, diversified equipment configurations can be carried out;

4. High output of single machine and low transportation cost

The maximum feed particle size is 75 cm, and the output can reach 320 tons per hour; materials can be directly processed on site to reduce transportation costs;

5. Oil and electricity dual-purpose, adjustable output

Diesel and electricity dual-purpose, power failure does not stop; no grating bar + self-flow tank design, the output can be adjusted to avoid over-crushing, and the grain shape is more round, which meets the requirements of high-standard materials.



产品参数

>> Product Parameters

型号 Model	配套型号 Matching model	配套设备 Matching equipment	进料粒度 Feed size (mm)	生产能力 Production capacity (t/h)	外形尺寸 Overall size (mm)
XGN-T150	ZGCX1038	XGN-Z1310	≤650	150-180	13500*2800*4500
XGN-T300	ZGCX1238	XGN-Z1512	≤750	250-320	13900*2800*5200
XGN-2470	4YK2470	-	-	150-280	14700*4200*7500

注：技术数据如有变更，恕不另行通知。Any change of technical data shall not be advised additionally.