

YKQ系列振动筛

YKQ series vibrating screen

YKQ系列圆振动筛俗称轻型筛或标准筛，采用先进的大游隙轴承脂，具有结构简单，性能稳定，筛分效果好等优点，适用于入料粒度 $\leq 200\text{mm}$ ，且分级粒度 $2\text{mm}-50\text{mm}$ 的各种筛分作业。

YKQ series circular vibrating screen, commonly known as light screen or standard screen, adopts advanced large clearance bearing, which has the advantages of simple structure, stable performance and good screening effect. It is suitable for feeding particle size $\leq 200\text{mm}$, and grading particle size $2\text{mm}-50\text{mm}$ various screening operations.



产品参数

>> Product Parameters

型号 Model	筛面层数 Number of sieve layers	筛网面积 Sieve area (m^2)	振幅 Amplitude (mm)	振动频率 Vibration frequency (r/min)	电机功率 Motor Power (kw)	处理能力 Capacity (t/h)
1YKQ1545	1	6.75	5-9	980	7.5	100-200
2YKQ1545	2	6.75	5-9	980	11	100-200
3YKQ1545	3	6.75	5-9	980	15	100-200
1YKQ1860	1	10.8	5-9	980	18.5	160-220
2YKQ1860	2	10.8	5-9	980	18.5	160-220
3YKQ1860	3	10.8	5-9	980	22	160-220
4YKQ1860	4	10.8	5-9	980	30	160-220
2YKQ2160	2	12.6	5-9	980	15	150-280
3YKQ2160	3	12.6	5-9	980	22	150-280
4YKQ2160	4	12.6	5-9	980	30	150-280
2YKQ2460	2	14.4	5-9	980	22	150-280
3YKQ2460	3	14.4	5-9	980	30	150-280
4YKQ2460	4	14.4	5-9	980	37	150-280
2YKQ2470	2	16.8	5-9	980	22	240-300
3YKQ2470	3	16.8	5-9	980	37	240-300
4YKQ2470	4	16.8	5-9	980	37	240-300
2YKQ3070	2	21	5-9	980	30	400-500
3YKQ3070	3	21	5-9	980	37	400-500
4YKQ3070	4	21	5-9	980	55	400-500

注：技术数据如有变更，恕不另行通知。Any change of technical data shall not be advised additionally.

注：表中未列出标准型单层圆振动筛规格型号，客户若需要单层圆振动筛，可参照双层振动筛参数，并定货告知。

Note: The specifications and models of the standard single-layer circular vibrating screen are not listed in the table. If customers need a single-layer circular vibrating screen, they can refer to the parameters of the double-layer vibrating screen and inform them when ordering.